



■ Features :

- Universal AC input / Full range (up to 295VAC)
- High efficiency 89%
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Built-in active PFC function
- IP67 design for indoor or outdoor installations
- UL1310 Class 2 power unit
- Pass LPS
- Cooling by free air convection
- 100% full load burn-in test
- High reliability
- Suitable for LED lighting and moving sign applications (Note.2)
- Compliance to worldwide safety regulations for lighting
- Suitable for dry / damp / wet locations
- 3 years warranty



LPS (for 48V only)



US (except for 48V)




SPECIFICATION


MODEL	CLG-60-12	CLG-60-15	CLG-60-20	CLG-60-24	CLG-60-27	CLG-60-36	CLG-60-48					
OUTPUT	DC VOLTAGE	12V	15V	20V	24V	27V	36V					
	CONSTANT CURRENT REGION Note.5	8.4 ~ 12V	10.5 ~ 15V	14 ~ 20V	16.8 ~ 24V	18.9 ~ 27V	25.2 ~ 36V					
	RATED CURRENT	5A	4A	3A	2.5A	2.3A	1.7A					
	CURRENT RANGE	0 ~ 5A	0 ~ 4A	0 ~ 3A	0 ~ 2.5A	0 ~ 2.3A	0 ~ 1.7A					
	RATED POWER	60W	60W	60W	60W	62.1W	61W					
	RIPPLE & NOISE (max.) Note.2	2Vp-p	2.4Vp-p	1.8Vp-p	2.7Vp-p	2.7Vp-p	3.6Vp-p					
	VOLTAGE ADJ. RANGE	11.5 ~ 13V	14.5 ~ 16.2V	19.5 ~ 22V	24 ~ 26V	25 ~ 30V	32.5 ~ 39V					
		Fixed can be modified between the range above										
	CURRENT ADJ. RANGE	Fixed. Can be modified between 3% ~ -25% rated output voltage										
	VOLTAGE TOLERANCE Note.3	±10%										
INPUT	LINE REGULATION	±3.0%										
	LOAD REGULATION	±5.0%										
	SETUP TIME	3000ms / 230VAC 5000ms / 115VAC at full load										
	VOLTAGE RANGE Note.4	90 ~ 295VAC 127 ~ 417VDC										
	FREQUENCY RANGE	47 ~ 63Hz										
	POWER FACTOR	PF ≥ 0.9 at 75 ~ 100% load, 115VAC / 230VAC										
	EFFICIENCY(Typ.)	85%	86%	87.5%	87%	88%	89%					
PROTECTION	AC CURRENT	0.8A/115VAC	0.4A/230VAC									
	INRUSH CURRENT(max.)	40A/230VAC										
	LEAKAGE CURRENT	<0.75mA / 240VAC										
	OVER CURRENT	95 ~ 110%										
		Protection type : Constant current limiting, recovers automatically after fault condition is removed										
	SHORT CIRCUIT	Hiccup mode, recovers automatically after fault condition is removed										
	OVER VOLTAGE	13.8 ~ 16V	17.5 ~ 21V	23 ~ 26V	28 ~ 32V	31 ~ 35V	41 ~ 46V					
ENVIRONMENT		Protection type : Shut down o/p voltage, re-power on to recover										
	OVER TEMPERATURE	12V: 90°C ±10°C (TSW1) detect on heatsink of power transistor										
		15V ~ 48V: 85°C ±10°C (TSW1) detect on heatsink of power transistor										
		Protection type : Shut down o/p voltage, recovers automatically after temperature goes down										
	WORKING TEMP.	-30 ~ +70°C (Refer to output load derating curve)										
	WORKING HUMIDITY	20 ~ 95% RH non-condensing										
	STORAGE TEMP., HUMIDITY	-40 ~ +80°C, 10 ~ 95% RH										
SAFETY & EMC	TEMP. COEFFICIENT	±0.03%/°C (0 ~ 50°C)										
	VIBRATION	10 ~ 500Hz, 5G 12min./1cycle, period for 72min. each along X, Y, Z axes										
	SAFETY STANDARDS	UL879, UL8750, UL1310 Class 2, TUV EN61347-1, EN61347-2-13 independent, CAN/CSA C22.2 No. 223-M91(except for 48V) ; J61347-1, J61347-2-13(20~27only), IP67 approved										
	WITHSTAND VOLTAGE	I/P-O/P:3.75KVAC I/P-FG:1.88KVAC O/P-FG:0.5KVAC										
	ISOLATION RESISTANCE	I/P-O/P:100M Ohms / 500VDC / 25°C / 70% RH										
	EMI CONDUCTION & RADIATION	Compliance to EN55015, EN55022 (CISPR22) Class B										
	HARMONIC CURRENT	Compliance to EN61000-3-2 Class C (≥75% load) ; EN61000-3-3										
OTHERS	EMS IMMUNITY	Compliance to EN61000-4-2,3,4,5,6,8,11; ENV50204, EN55024, EN61547, light industry level (surge 4KV), criteria A										
	MTBF	495.7Khrs min. MIL-HDBK-217F (25°C)										
	DIMENSION	195.6*61.5*38.8mm (L*W*H)										
NOTE	PACKING	0.86Kg; 16pcs/14.8Kg/0.54CUFT										
		1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. Direct connecting to LEDs is not suggested for models with "RIPPLE & NOISE" >±10% and using additional drivers is highly recommended. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. Derating may be needed under low input voltage. Please check the static characteristics for more details. 5. Constant current operation region is within 70% ~100% rated output voltage. This is the suitable operation region for LED related applications, but please reconfirm special electrical requirements for some specific system design. 6. The power supply is considered as a component that will be operated in combination with final equipment. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.										

Mechanical Specification


Case No. 957A Unit:mm



Block Diagram



Derating Curve



Static Characteristics

